

Touch sensitive Door Access Units.

The range of touch sensitive Door Access systems provide the means to be able to control visitors to your premises through the convenience of your telephone system. The models available cater for both Visitor and Staff Access and also offers the ability to view visitors via your Internal PC network.

Features:

Communicate with visitors to your premises via any handset on your telephone system.

Open the door release via the telephone keypad.

Transfer the visitor call to any other handset.

Day / Night Mode. The systems allow the user to manually program the system to call different extensions at different times of the day.

Staff Access is possible via 4 x 4 digit access codes.

Robust design. The units use touch sensitive buttons and are vandal resistant.

Location. The units are designed for both internal and external applications.

User programmable through touch tone DTMF dialling on the telephone system.

Password protection. Access to the unit programming is via a 4 digit code.

Video Option. This allows visitors to be viewed via an Internal pin hole colour camera.

Viewed on a Network PC. Visitors can be viewed on any PC with the optional video interface and software.

Direct Dial of extensions. When programmed, the Staff access keypad can also direct dial any other extension on the telephone system.

Speed Dial. The keypad can be programmed to offer up to 8 speed dials $+\ 1$ access code.

Flush and Surface versions. Both are available to suit all requirements.

Benefits:

Prevents unauthorised access to your premises.

Protects staff and equipment from opportunist theft.

Allows desktop control of the system, therefore allowing staff to be more efficient.

Scaleable solution. The system can be upgraded to include Video options and can interface with a wide range of door releases and locking mechanisms.









How they work:

The intercom units connect to the telephone system as an analogue extension.

On arrival, Visitors will press the call button and the unit will dial an extension, or group of extensions if set up as a hunt group.

The operator will pick up the intercom call and have 2 way speech with the visitor. The operator can then choose to attend to the visitor or transfer the call to their colleague as required.

The operator can then press a pre programmed number on the telephone keypad and the intercom will then activate the door release, allowing the visitor access to the premises.

If the video option is selected, in addition to allowing 2 way speech, the operator can view the visitor on their network PC via the video interface.

If the staff access option is selected, the unit comes with a touch sensitive keypad and allows both direct dialling of extensions and 4 staff entry codes to be programmed, therefore allowing staff access to the premises without the need to communicate with an operator.

Intercom Components:

Visitor Access Control Package:





Features:

- * Single button, touch sensitive intercom unit.
- * Surface + Flush Mount, tough vandal resistant Casing machined out of solid aluminium.
- * Sleek, Modern design.
- * Day and night operating modes.
- * Connects to PABX Analogue extension port.
- * Operation & Programming via DTMF tones.
- * 12 months return to base Warranty.

Visitor + Staff Access Control Package:





Features:

- * As Visitor package, with an additional keypad.
- * Allows staff access via 4 x 4 digit entry codes.
- * Allows direct dialling of PABX extensions.
- * Allows up to 9 programmable speed dials.
- * Both Visitor + Staff access units have the option to install a colour pin hole camera.
- * Allows desktop control of system allowing staff to be more efficient.
- * Scaleable solution allows the system to change to suit future requirements.

Authorised Dealers & Distributors:





Video Components:

Pin Hole Camera + Web interface:





Features:

- * Visitor or Visitor + Staff Access intercom units are able to be upgraded by the addition of a Colour pin hole camera.
- * Web Interface unit allows real time images of visitors viewed on the inbuilt colour camera to be viewed on the PC screen.
- * Provides a means of visual verification and therefore an additional level of security.
- * Compatible with any customer supplied LAN PC.

Viewing Software:



Features:

- * 1 Camera recording at up to 25fps.
- * Continuous, Scheduled and Motion Detection Recording.
- * MPEG4 Compression.
- * Single camera live viewing and playback.
- * Quick searching of recordings by motion detection list or time/date.
- * Easy exporting and backup of recordings to CD or Hard Drive
- Remote viewing and playback from a PC on the same LAN.

Unit Specifications:

Dimensions - (H) x (W) x (D)

- * Surface Pantel / Pancode: 200 x 106 x 25 (mm)
- * Flush Pantel / Pancode: 232 x 137 x 25 (mm)
- * Construction: Solid Anodised Aluminium
- * Signalling: DTMF
- * PABX Connection Port : Analogue Extension
- * IP Rating: 35
- * Back ground Lighting: No
- * Power Requirement:: 12VDC 1 A
- * Release contacts: Relay NO / NC